



T174 OFF THE BOARD

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE: T174
PRODUCT NAME: OFF THE BOARD
MANUFACTURER: Selden Research Limited
Staden Lane
Ashbourne Road
Buxton
Derbyshire
SK17 9RZ

TELEPHONE: 01298 26226
FAX: 01298 26540
EMAIL: safety@selden.co.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME CAS No.:	EINECS Nr.:	CLASSIFICATION	CONTENT
1-METHOXY-2-PROPANOL 107-98-2	203-539-1	R10	5-10 %

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

4. FIRST AID MEASURES

INGESTION: DO NOT INDUCE VOMITING!, Rinse mouth thoroughly. Drink plenty of water. Get medical attention.
SKIN: Rinse with water. Get medical attention if any discomfort continues.
EYES: Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS: Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.
ENVIRONMENTAL PRECAUTIONS: Any spillage needs to be contained and not allowed to enter water courses

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Eye protection should be considered where there is a risk of splashing. Rubber gloves and barrier cream are recommended when using any chemical.
STORAGE PRECAUTIONS: Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
1-METHOXY-2-PROPANOL		WEL	375 mg/m3	560 mg/m3(Sk)

PROTECTIVE EQUIPMENT:





T174 OFF THE BOARD

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear, Liquid
COLOUR:	Yellow
ODOUR:	Slight odour of alcohol
BOILING POINT (°C):	> 100
BULK DENSITY:	0.959 kg/l
pH-VALUE, CONC. SOLUTION:	7.0
SOLUBILITY:	Soluble in water
FLASH POINT (°C):	>70 CC (Closed)

10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions.
CONDITIONS TO AVOID:	Avoid excessive heat for prolonged periods of time.
HAZARDOUS COMPOSITION PRODUCTS:	Not known.

11. TOXICOLOGY INFORMATION

INGESTION:	Liquid irritates mucous membranes and may cause abdominal pain if swallowed. Diarrhoea. Nausea, vomiting.
SKIN CONTACT:	Prolonged contact may cause dryness of the skin.
EYE CONTACT:	Irritation is likely.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Not classed as Hazardous to the Environment but release to the environment should be avoided.
--------------	---

13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Dispose of waste and residues in accordance with local authority requirements.
---------------------	--

14. TRANSPORT INFORMATION

ROAD TRANSPORT NOTES:	Not Classified
RAIL TRANSPORT NOTES:	Not Classified.
SEA TRANSPORT NOTES:	Not Classified.
AIR TRANSPORT NOTES:	Not Classified.

15. REGULATORY INFORMATION

RISK PHRASES:	NC Not classified.
SAFETY PHRASES:	P13 Safety data sheet available for professional user on request. S2 Keep out of the reach of children, S23 Do not breathe vapour/spray. S37/39 Wear suitable gloves and eye/face protection. S51 Use only in well-ventilated areas.
STATUTORY INSTRUMENTS:	Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

USER NOTES:	The following risk phrases relate to the raw materials in the product and not the product itself:-
REVISION DATE:	07/03/2008
REV. NO./REPL. SDS GENERATED:	4
R-PHRASES (Full Text):	R10 Flammable.